## Smarter Multi-Touch Experience

## **ULTRA HD MULTI-TOUCH SIGNAGE 84WT70**



#### **ULTRA HD MULTI TOUCH SIGNAGE**

It can effectively increase attention and concentration in a spacious room using Ultra HD supported bigscreen HD TV. It is especially suitable for interactive communication locations such as medium to large classrooms, conference rooms, museums, shopping malls, and information desks.



#### **GHOST FREE MULTI-TOUCH**

When you touch it, it is possible to express your writing or drawing crisp and clean without shaking using 'No Ghosting!



Competitor Ghosting



LG Ghost-free

#### **10 POINT MULTI-TOUCH**

Because there is no need for a separate pen, you can easily utilize it with the touch of your hands. It provides a more realistic sense of touch since it can sense 10 simultaneous touches at once.











## **ULTRA HD MULTI-TOUCH SIGNAGE**

# 84WT70 84U"



Providing the peak in picture clarity featuring Ultra HD technology, which quadruples FULL HD resolution to 8 million pixels

## **FEATURES**

#### **IPS Panel**

- Low Screen Temperature on Standard Mode
- No Blackening Effect
- Wide Viewing Angle

## Multi Touch

- IR Spread Type
- 10 Point Multi Touch
- No Additional Pen Needs



• UD Contents Playback

## **SPECIFICATIONS**

#### 84WT70MS / 84WT70PS

			040017010137040017013
PANEL	Screen Size		84U"
	Panel Technology		IPS
	Aspect Ratio		16:9
	Native Resolution		3,840 x 2,160 (Ultra HD)
	Brightness		350 cd/m <sup>2</sup> Typ
	Contrast Ratio		1,400:1
	Dynamic CR		500,000:1
	Viewing Angle (H x V)		178 x 178
	Response Time		12ms (G to G) Typ
CONNECTIVITY	Input (Rear)	Digital	HDMI (2), DVI-D (1), Display Port (1) with HDCP for all Input
		Analog	RGB (1), Composite (1)
		Audio	RGB / DVI-D / AV
		External Control	RS232C (1), RJ45 (1), IR (1, Internal)
		USB	USB 2.0 x 2
		HDTV Formats	Composite : 576i
			HDMI: 720p, 1080i, 1080p, 2160p
	Output (Rear)	Digital	DVI-D (1)
		Analog	RGB (1)
		Audio	Yes (1), Line Out (1)
		External Control	Main : RS232C (1), IR (1, Internal)
PHYSICAL	Bezel Width		34.0mm
SPECIFICATION	Monitor Dimension (W x H x D)		1,951 x 1,137 x 112
	Weight (Head)		102.6kg
	Carton Dimensions (W x H x D)		2,050 x 1,261 x 330
	Packed Weight		118.0kg
	VESA™ Standard Mount Interface		600 x 400, M8
SPECIAL FEATURES	Temperature Sensor		Yes
	Auto Brightness Sensor		Yes
	Brightness / Contrast / Backlight		Yes
	Position / Size		Yes
	Auto Config / Phase		Yes
	Energy Saving		Yes (Minimum, Medium, Maxium)
	Smart Energy Saving		Yes

ENVIRONMENT CONDITIONS	Operation Temperature		0 °C to 40 °C
	Operation Humidity		10 % to 80 %
POWER	Power Supply		100~240V, 50/60Hz
		Тур	350W
	Power	Smart Energy Saving	200W
	Consumption	DPM	1.5W
		Power off	0.5W
STANDARD	Safety		UL, cUL, CB scheme, TUV (TBD)
(CERTIFICATION)	EMC		FCC Class "A", VCCI, C-tick, CE, KCC (TBD)
	ErP / Energy Star		Yes / No
MEDIA PLAYER	Slot PC Compatible (Optional)		Yes (MP700, MP500)
COMPATIBILITY	External Media Player Attatchable		No
SOFTWARE	Touch Screen Writing Software		Yes (only 84WT70PS)
COMPATIBILITY			
ACCESSORY	Included		D-Sub Cable, Power Cord,
			Remote Controller (incl. Battery 2ea),
			CD (Manual / Writing Software / ESG), Eye Bolt 2ea
	Optional	Media Player	MP700, MP500
		Speaker	SP-2000
		Wall Mount	LSW630
TOUCH	Available Obje	ect Size for Touch	Ø6 mm
	Accuracy		1mm
	Interface		USB 2.0
	Power		5W
	Protection Glass Thickness		5T (Anti-Fog, Anti-Reflection)
	Protection Glass Transmission		85% (TBD)
	Operating System Support		Windows XP (1 Point) / Windows 7 (10 Point)
	Multi Touch Point		Max 10 Point

 $<sup>* \</sup> Image \ may \ differ \ slightly \ from \ actual \ product. \ Specifications \ are \ subject \ to \ change \ without \ prior \ notice.$ 

#### **DIMENSION** (unit:mm)







