



PX112 MK2

Loudspeaker cabinet 12" 2-way

► Features

- 2 - Way system
- 300 Watt RMS Power
- High-fidelity, full range reproduction of music and speech
- Vertical or horizontal mounting
- Coverage pattern 90° x 75° (Rotatable horn)
- Integrated rigging points & carry handles
- Stand fitting pole adapter (35 mm)
- Scratch-free EPDM coating

► Applications

- Concerts
- Clubs
- Pubs
- Indoor festivals
- Athletic fields
- Events



The PX Series are compact full range loudspeaker cabinets for a wide variety of indoor applications. They come in four different models, each of them with different size and performance meeting the requirements for every specific application.

The PX112MK2 is the 12" model of the PX family, consisting of a 12" high output woofer and a compression driver with 1.3" voice coil. The compression driver is fitted with a 90° x 75° coverage horn which can be rotated allowing both horizontal and vertical use.

Thanks to the high quality components and an accurately optimized integrated passive crossover network with tweeter overload protection, the PX112MK2 delivers a clear and natural sound with an RMS power of 300 Watt and a maximum power of 600 Watt. The frequency range (-10 dB) starts from 55 Hz up to 20 kHz and the sensitivity (1W / 1m) reaches 100 dB while a maximum continuous sound pressure level from 125 dB can be achieved.

The construction of the cabinets is made of medium density fibreboard with a durable textured and scratch resistant EPDM coating. The front side of the cabinet is finished with a powder coated steel grill lined with acoustically transparent backing.

Recessed carry handles on both sides of the cabinet make carrying easy. Positioning and suspension of the speaker is easily achieved by using the standard 35 mm pole adapter on the bottom side and M10 rigging points. An optional mounting bracket provides a complete solution for wall mounting. Two speaker connectors on the rear side of the cabinet provide reliable connections with easy link-through to other cabinets.

► Specifications

SYSTEM SPECIFICATIONS		
Speaker Type	2 - Way	
Max Power	600 Watt	
RMS Power	300 Watt	
Impedance	8 Ohm	
Sensitivity (1W / 1m)	100 dB	
Max continuous SPL (RMS W / 1 m)	125 dB	
Frequency Response (±3dB)	70 Hz - 19 kHz	
Frequency Range (-10dB)	55 Hz - 20 kHz	
Crossover Frequency	2 kHz	
Crossover Type	Passive built-in	
Horizontal Dispersion	90°	
Vertical Dispersion	75°	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	383 x 643 x 420 mm	
Weight Net	26 Kg	
Connection	2 x Speakon compatible (Linkthrough)	
Drivers	HF	1.3" Compression driver
	MF	12"
Construction	Medium density fibreboard with textured EPDM coating	
Grill type	Powder coated steel grill with lining	
Mounting & Handling	Rigging points	8 x M10
	Stand fitting	35 mm pole adapter on bottom M10 screw flange on top
	Carry handle(s)	On both sides
Available versions	Black (RAL9005)	PX112MKII
	White (RAL9010)	PX112MKII/W
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping Weight & Volume	29 Kg - 0.17 Cbm	
Optional Accessories	CPB112P Protective cover bag	
	MBK112 Wall mounting bracket	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		

► Architects' and Engineers' Specifications

The speaker cabinet shall be a 2-way full range system and have the following dimensions: W 383 x H 643 x D 420 mm. Its weight shall not exceed 28 kg. The cabinet shall be constructed of medium density fibreboard with a durable scratch proof EPDM coating. The front side shall be finished with a powder coated steel grill which is lined with an acoustical transparent backing.

The cabinet shall have a recessed carry handles on both sides of the cabinet for easy handling, while a standard 35 mm pole adapter and 8 x M10 rigging points shall be provided for positioning and suspension of the speaker.

It shall have an RMS power handling of 300 Watt with a maximum power handling of 600 Watt. The frequency response (-10 dB) shall range from 55 Hz to 20 kHz. The sensitivity shall be 100 dB when measuring with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level shall achieve 125 dB.

The loudspeaker shall consist of a 1.3" HF compression driver and a 12" medium frequency range loudspeaker. It shall have an impedance of 8 Ohm and contain a passive built-in crossover network with a crossover frequency of 2 kHz. The complete model is constructed of high-quality components. It shall also have an integrated tweeter overload protection circuit. The horn mounted on the HF driver shall have a horizontal dispersion of 90° and a vertical dispersion of 75° and shall be rotatable allowing both horizontal and vertical use. Connections with the speaker shall be made using 2 x speaker connectors allowing easy connection and linkthrough.

► Technical drawing

